ProLite L403W | 100 cm

The new Prolite L403W offers excellent image quality as either a computer monitor or as a TV. With 2 x7W stereo speakers (NICAM Stereo) excellent sound quality is assured. In addition Faroujda technolgy means that moving images appear crisp and clear.

Technical data	
Panel	a-Si Active Matrix
Diameter	101 cm (39.6")
Display area h x w	862 x 517 mm
Contrast ratio	600 : 1 typical
Brightness (nominal)	550 cd / m2 typical
Response time	22 msec
Viewing zone	Horizontal: 170° Vertical: 170°
Display colors	16 Mio.
Pixel pitch h x v	0.6735 x0.6735 mm
TV-Standard	PAL / NTSC / SECAM
Sound	2 x 7W
Inputs	1 x DVI-I, SCART (Composite / RGB), RCA, S-Video
Teletext	Yes
PIP (Picture in Picture)	Yes
Remote control	Yes
Horizontal sync	31.47 - 60.24 KHz
Vertical sync	56 - 75 Hz
Bandwith	103 MHz
Physical resolution	1280 x 768
Input connector	DVI-I, SCART (Composite / RGB), RCA, S-Video
Syncronisation	Seperate and composite sync
Plug & play	DDC2B
Speaker	2 x 7W
User controls	Brightness, Contrast, H / V Position, Clock, Phase, Treble, Bass, Surround Sound, OSD Position, Full Screen, Economy Mode, Lauguage, Reset, WXGA, Sharpness, Auto Balance, PIP, PIP Control TV Brightness, Contrast, Sharpness, Colour, Tint, Treble, Bass, Surround Sound, OSD Position, Full screen, Economy, Video Mode, Lauguage, Reset, Film Mode, Enhancer, Noise Reducer, Auto Tune, Manual Tune, Channel move
Safety	CE, TUV-GS / MPR III
power supply	Worldwide 100-230VAC, 50-60Hz input
Power usage	180W maximum in normal use, 5W in suspend mode
Power management	180W maximum in normal use, 5W in suspend mode
Dimensions w x h x d	1140 x 640 x 300 With Stand mm
Weight	38 kg

Version 8/2004, changes and mistakes reserved.